acc. to 29 CFR 1910.1200 App D



SpatterMist

Version number: 2.0 Revision: 2024-04-11 Replaces version of: 2024-04-11 (1)

SECTION 1: Identification

1.1 Product identifier

Trade name SpatterMist

Alternative number(s) XB2970, XB2970TOTE

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses general use

1.3 Details of the supplier of the safety data sheet

Techniweld USA 3940 Stern Ave St. Charles IL 60174 United States

Telephone: 630-232-6421 Website: www.twusa.com

Email: info@ChemisphereCorp.com

1.4 Emergency telephone number

Emergency information service CHEMTREC: 800-424-9300 (24 Hour)

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and cat- egory	Hazard state- ment
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
A.3	serious eye damage/eye irritation		Eye Dam. 1	H318
A.9	A.9 specific target organ toxicity - repeated exposure		STOT RE 2	H373
B.6	flammable liquid	4	Flam. Liq. 4	H227

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects


Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

United States: en Page: 1 / 17





SpatterMist

Version number: 2.0 Revision: 2024-04-11 Replaces version of: 2024-04-11 (1)

- Pictograms

GHS05, GHS08



- Hazard statements

H227 Combustible liquid. H315 Causes skin irritation. H318 Causes serious eye damage.

H373 May cause damage to organs through prolonged or repeated exposure.

- Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray. P280 Wear protective gloves/eye protection/face protection.

If on skin: Wash with plenty of water. P302+P352

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and P305+P351+P338

easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor. P321 Specific treatment (see on this label).

P362 Take off contaminated clothing and wash before reuse.

In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish. P370+P378

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for

labelling

Polyethylene glycol octylphenyl ether, Ethylenediaminetetraacetic acid,

tetrasodium salt, MONOETHANOLAMINE 99%

2.3 Other hazards

This material is combustible, but will not ignite readily.

SECTION 3: Composition/information on ingredients

3.1 **Substances**

Not relevant (mixture)

3.2 **Mixtures**

Description of the mixture

Name of substance	Ider	ntifier	Wt%
Polyethylene glycol octylphenyl ether	CAS No	9002-93-1	10 - < 25
DPM Dipropylene Glycol Methyl	CAS No	34590-94-8	5 - < 10
MONOETHANOLAMINE 99%	CAS No	141-43-5	1-<5
Ethylenediaminetetraacetic acid, tetrasodium salt	CAS No	64-02-8	1-<5

Remarks

For full text of abbreviations: see SECTION 16

United States: en Page: 2 / 17



acc. to 29 CFR 1910.1200 App D

SpatterMist

Version number: 2.0 Revision: 2024-04-11 Replaces version of: 2024-04-11 (1)

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

United States: en Page: 3 / 17



acc. to 29 CFR 1910.1200 App D

SpatterMist

Version number: 2.0 Revision: 2024-04-11 Replaces version of: 2024-04-11 (1)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

United States: en Page: 4 / 17

acc. to 29 CFR 1910.1200 App D



SpatterMist

Version number: 2.0 Revision: 2024-04-11 Replaces version of: 2024-04-11 (1)

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Control of the effects

Protect against external exposure, such as

frost

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Coun- try	Name of agent	CAS No	Identi- fier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Nota- tion	Source
US	ethanolamine	141-43-5	REL	3 (10 h)	8 (10 h)	6	15				NIOSH REL
US	ethanolamine	141-43-5	TLV®	3		6					ACGIH® 2024
US	ethanolamine	141-43-5	PEL	3	6						29 CFR 1910.100 0
US	ethanolamine (2- aminoethanol)	141-43-5	PEL (CA)	3	8	6	15				Cal/ OSHA PEL
US	dipropylene glycol methyl ether	34590-94-8	PEL (CA)	100	600	150	900				Cal/ OSHA PEL
US	dipropylene glycol methyl ether	34590-94-8	REL	100 (10 h)	600 (10 h)	150	900				NIOSH REL
US	dipropylene glycol methyl ether	34590-94-8	PEL	100	600						29 CFR 1910.100 0

United States: en Page: 5 / 17

acc. to 29 CFR 1910.1200 App D



SpatterMist

Version number: 2.0 Replaces version of: 2024-04-11 (1) Revision: 2024-04-11

Occupational exposure limit values (Workplace Exposure Limits)

Coun- try	Name of agent	CAS No	Identi- fier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [mg/m³]	Source
US	dipropylene glycol methyl ether (DP- GME)	34590-94-8	TLV®	50					ACGIH® 2024

Notation

Ceiling-C STEL

ceiling value is a limit value above which exposure should not occur short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified TWA


Relevant DNELs of components

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DPM Dipropylene Glycol Methyl	34590-94-8	DNEL	308 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic ef- fects
DPM Dipropylene Glycol Methyl	34590-94-8	DNEL	283 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic ef- fects
MONOETHANOLAM- INE 99%	141-43-5	DNEL	1 mg/m³	human, inhalatory	worker (industry)	chronic - systemic ef- fects
MONOETHANOLAM- INE 99%	141-43-5	DNEL	0.51 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
MONOETHANOLAM- INE 99%	141-43-5	DNEL	3 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic ef- fects
Ethylenediaminetet- raacetic acid, tetraso- dium salt	64-02-8	DNEL	1.5 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
Ethylenediaminetet- raacetic acid, tetraso- dium salt	64-02-8	DNEL	3 mg/m³	human, inhalatory	worker (industry)	acute - systemic ef- fects
Ethylenediaminetet- raacetic acid, tetraso- dium salt	64-02-8	DNEL	1.5 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
Ethylenediaminetet- raacetic acid, tetraso- dium salt	64-02-8	DNEL	3 mg/m³	human, inhalatory	worker (industry)	acute - local effects

Relevant PNECs of components

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
DPM Dipropylene Glycol Methyl	34590-94-8	PNEC	19 ^{mg} / _l	aquatic organisms	freshwater	short-term (single in- stance)

United States: en Page: 6 / 17





SpatterMist

Version number: 2.0 Revision: 2024-04-11


Replaces version of: 2024-04-11 (1) Relevant PNECs of components Name of substance CAS No **Endpoint** Threshold **Environmental com-**Organism **Exposure time** level partment DPM Dipropylene 34590-94-8 **PNEC** 1.9 mg/_I aquatic organisms marine water short-term (single in-Glycol Methyl stance) DPM Dipropylene 34590-94-8 **PNEC** 4,168 ^{mg}/_l aquatic organisms sewage treatment short-term (single in-Glycol Methyl plant (STP) stance) DPM Dipropylene $70.2 \frac{mg}{ka}$ 34590-94-8 **PNEC** aquatic organisms freshwater sediment short-term (single in-Glycol Methyl stance) $7.02 \, \frac{mg}{ka}$ aquatic organisms DPM Dipropylene 34590-94-8 **PNFC** marine sediment short-term (single in-Glycol Methyl stance) 2.74 ^{mg}/_{kq} DPM Dipropylene 34590-94-8 **PNEC** terrestrial organsoil short-term (single in-Glycol Methyl isms stance) MONOETHANOLAM-141-43-5 **PNEC** $0.07 \frac{mg}{I}$ aquatic organisms freshwater short-term (single in-**INE 99%** stance) MONOETHANOLAM-141-43-5 0.007 mg/I short-term (single in-**PNEC** aquatic organisms marine water **INE 99%** stance) MONOETHANOLAM-141-43-5 **PNEC** 100 mg/i aquatic organisms sewage treatment short-term (single in-**INE 99%** plant (STP) stance) 0.357 mg/kg MONOETHANOLAM-141-43-5 short-term (single in-**PNEC** freshwater sediment aquatic organisms **INE 99%** stance) 0.036 mg/kg MONOETHANOLAMshort-term (single in-141-43-5 **PNEC** aquatic organisms marine sediment **INE 99%** stance) 1.29 mg/kg MONOETHANOLAM-141-43-5 **PNEC** terrestrial organsoil short-term (single in-**INE 99%** stance) isms Ethylenediaminetet-64-02-8 **PNEC** 2.83 mg/_I aquatic organisms freshwater short-term (single inraacetic acid, tetrasostance) dium salt 0.283 mg/_I Ethylenediaminetet-64-02-8 **PNEC** short-term (single inaquatic organisms marine water raacetic acid, tetrasostance) dium salt Ethylenediaminetet-50 mg/i short-term (single in-64-02-8 **PNEC** aquatic organisms sewage treatment raacetic acid, tetrasoplant (STP) stance) dium salt 1.1 ^{mg}/_{kg} Ethylenediaminetet-64-02-8 **PNEC** terrestrial organshort-term (single insoil raacetic acid, tetrasoisms stance) dium salt

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

United States: en Page: 7 / 17





SpatterMist

Version number: 2.0 Revision: 2024-04-11 Replaces version of: 2024-04-11 (1)

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection. Use safety goggle with side protection. Wear face-shield.

Skin protection

- Hand protection

Wear suitable gloves.

- Other protection measures

Wash hands thoroughly after handling. Protective clothing against liquid chemicals. Footwear protecting against chemicals.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties


Appearance

Physical state	liquid		
Color	not determined		
Particle	not relevant (liquid)		
Odor	characteristic		

Other safety parameters

pH (value)	not determined		
Melting point/freezing point	not determined		
Initial boiling point and boiling range	100 °C		
Flash point	75 °C at 1,013 mbar		
Evaporation rate	not determined		
Flammability (solid, gas)	not relevant, (fluid)		
Vapor pressure	10 mmHg at 75.1 °C		

United States: en Page: 8 / 17





SpatterMist

Version number: 2.0 Revision: 2024-04-11

Replaces version	of: 2024-04-11	(1)
------------------	----------------	-----

Density	8.47 ^{lb} / _{gal}
Vapor density	this information is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	207 °C
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Liquid content	95.26 %
Solid content	2.51 %
Temperature class (USA, acc. to NEC 500)	T3 (maximum permissible surface temperature on the equipment: 200°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

United States: en Page: 9 / 17

acc. to 29 CFR 1910.1200 App D



SpatterMist

Version number: 2.0 Revision: 2024-04-11 Replaces version of: 2024-04-11 (1)

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if swallowed.

Acute toxicity estimate (ATE) of components			
Name of substance	CAS No	Exposure route	ATE
Polyethylene glycol octylphenyl ether	9002-93-1	oral	500 ^{mg} / _{kg}
MONOETHANOLAMINE 99%	141-43-5	oral	1,089 ^{mg} / _{kg}
MONOETHANOLAMINE 99%	141-43-5	inhalation: vapor	11 ^{mg} / _l /4h
Ethylenediaminetetraacetic acid, tetrasodium salt	64-02-8	oral	>1,780 ^{mg} / _{kg}
Ethylenediaminetetraacetic acid, tetrasodium salt	64-02-8	inhalation: dust/mist	>1.5 ^{mg} / _l /4h

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

United States: en Page: 10 / 17

acc. to 29 CFR 1910.1200 App D



SpatterMist

Version number: 2.0 Revision: 2024-04-11 Replaces version of: 2024-04-11 (1)

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
DPM Dipropylene Glycol Methyl	34590-94-8	LC50	>1,000 ^{mg} / _l	fish	96 h
DPM Dipropylene Glycol Methyl	34590-94-8	ErC50	>969 ^{mg} / _l	algae	72 h
DPM Dipropylene Glycol Methyl	34590-94-8	EC50	>969 ^{mg} / _l	algae	72 h
MONOETHANOLAMINE 99%	141-43-5	LC50	349 ^{mg} / _l	fish	96 h
MONOETHANOLAMINE 99%	141-43-5	EC50	27.04 ^{mg} / _l	aquatic invertebrates	48 h
MONOETHANOLAMINE 99%	141-43-5	ErC50	2.8 ^{mg} / _l	algae	72 h
Ethylenediaminetet- raacetic acid, tetrasodi- um salt	64-02-8	LC50	>100 ^{mg} / _l	fish	96 h
Ethylenediaminetet- raacetic acid, tetrasodi- um salt	64-02-8	EC50	>114 ^{mg} / _l	aquatic invertebrates	48 h
Ethylenediaminetet- raacetic acid, tetrasodi- um salt	64-02-8	ErC50	>60 ^{mg} / _l	algae	72 h

Aquatic toxicity (chro	onic) of compone	ents			
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
MONOETHANOLAMINE 99%	141-43-5	EC50	2.5 ^{mg} / _l	aquatic invertebrates	21 d

United States: en Page: 11 / 17

acc. to 29 CFR 1910.1200 App D



SpatterMist

Version number: 2.0 Revision: 2024-04-11 Replaces version of: 2024-04-11 (1)

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1	UN number	not assigned
14.2	UN proper shipping name	not relevant
14.3	Transport hazard class(es)	none

14.4 Packing group not assigned

14.5 Environmental hazards non-environmentally hazardous acc. to the dangerous goods regula-

tions

14.6 Special precautions for user

Do not handle until all safety precautions have been read and understood. .

14.7 Information for each of the UN Model Regulations


Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

United States: en Page: 12 / 17





SpatterMist

Version number: 2.0 Revision: 2024-04-11 Replaces version of: 2024-04-11 (1)

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA)

all ingredients are listed (ACTIVE) or exempt from

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313) none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
DPM Dipropylene Glycol Methyl	34590-94-8		F2
MONOETHANOLAMINE 99%	141-43-5		CO F2

Legend

CO Corrosive

F2 Flammable - Second Degree

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

Drug precursors, Chemicals designated within the Controlled Substances Act, 21 U.S.C. § 802, paragraphs 34 (list I) and 35 (list II)

none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

United States: en Page: 13 / 17

acc. to 29 CFR 1910.1200 App D



SpatterMist

Version number: 2.0 Revision: 2024-04-11 (1)

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temper- atures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temper- atures before ignition can occur
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)

United States: en Page: 14 / 17





SpatterMist

Version number: 2.0 Revision: 2024-04-11 Replaces version of: 2024-04-11 (1)

Legend

Australian Inventory of Industrial Chemicals Chemical Inventory and Control Regulation List of Existing and New Chemical Substances (CSCL-ENCS) AIIC CICR

CSCL-ENCS

DSL Domestic Substances List (DSL)

EC Substance Inventory (EINECS, ELINCS, NLP) **ECSI**

IECSC Inventory of Existing Chemical Substances Produced or Imported in China

INSQ National Inventory of Chemical Substances National Inventory of Chemical Substances
Korea Existing Chemicals Inventory
New Zealand Inventory of Chemicals
Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH registered substances KECI[^] NZIoC

PICCS

REACH Reg.

Taiwan Chemical Substance Inventory TCSI

TSCA Toxic Substance Control Act

Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-rel- evant
2.2	- Hazardous ingredients for labelling: IGEPAL CA 630, Ethylenediaminetetraacetic acid, tetrasodium salt, MONOETHANOLAMINE 99%	- Hazardous ingredients for labelling: Polyethylene glycol octylphenyl ether, Ethylene- diaminetetraacetic acid, tetrasodium salt, MONO- ETHANOLAMINE 99%	yes
3.2		Description of the mixture: change in the listing (table)	yes
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)	yes
11.1		Acute toxicity estimate (ATE) of components: change in the listing (table)	yes
11.1		IARC Monographs on the Evaluation of Carcinogen- ic Risks to Humans: change in the listing (table)	yes
12.1		Aquatic toxicity (acute) of components: change in the listing (table)	yes
12.1		Aquatic toxicity (chronic) of components: change in the listing (table)	yes
15.1	Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)		yes
15.1	List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)		yes
15.1		List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4): change in the listing (table)	yes
15.1		Hazardous Substance List (NJ-RTK): change in the listing (table)	yes

United States: en Page: 15 / 17

acc. to 29 CFR 1910.1200 App D



SpatterMist

Version number: 2.0 Revision: 2024-04-11 (1)

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH® 2024	From ACGIH®, 2024 TLVs® and BEIs® Book. Copyright 2024. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
STEL	Short-term exposure limit

United States: en Page: 16 / 17





SpatterMist

Version number: 2.0 Revision: 2024-04-11

Replaces version of: 2024-04-11 (1)

Abbr.	Descriptions of used abbreviations
TLV®	Threshold Limit Values
TWA	Time-weighted average

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H227	Combustible liquid.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H373	May cause damage to organs through prolonged or repeated exposure.

Disclaimer

The information and recommendations contained in the Safety Data Sheet (SDS) are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. The information and recommendations set forth herein are presented in good faith and believed to be correct as of this date hereof.

Techniweld USA, however, makes no representation as to the completeness or accuracy thereof, and information is supplied upon the express condition that the persons receiving the information will be required to make their own determination as to its suitability for their purposes prior to use. In no event will Techniweld USA be responsible for any damages of any nature whatsoever resulting from the use of, reliance upon, or the misuse of this information. User assumes all risk of use, storage and handling of the product in compliance with applicable federal, state and local laws and regulations.

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTIC-ULAR PURPOSE, OR OF ANY OTHER NATURE, ARE MADE BY TECHNIWELD USA HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH THE INFORMATION REFERS. The information as supplied herein is simply to be informative and intended solely to alert the user of the substance, which is the subject matter of this SDS. The ultimate compliance with federal, state or local regulations concerning the use of this compound, or compliance with respect to product liability, rests solely upon the purchaser thereof.

This information relates to the material designated and may not be valid for such material used in combination with any other materials nor in any process.

United States: en Page: 17 / 17